

SRP-350V

3-inch Thermal POS Printer



Print Characteristics

Print Method

Direct Thermal

Print Speed

SRP-350V: Up to 300 mm/sec

SRP-352V: Up to 270 mm/sec

Print Resolution

SRP-350V: 180 dpi

SRP-352V: 203 dpi

Print Width

Up to 72 mm

Sensor

Paper End, Paper Near End, Cover Open,
Visibility Intelligence Sensor

Media Characteristics

Media Type

Receipt

Media Width

80 mm

Optional 58 mm using 2-inch Partition

Media Roll Diameter

Up to 83 mm

Media Thickness

0.05 to 0.08 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (W x L x H)

145 x 204 x 146 mm (5.7 x 8.03 x 5.74 inch)

Weight

1.6 kg (3.52 lbs.)

Electrical

EnergyStar® Certified,
External Power Adapter 100-240 VAC,
50/60 Hz

Drawer Port

2 ports (Via Y-Type Adapter)

Performance Characteristics

Memory

64 MB SDRAM, 64 MB Flash

NV Image Memory

256 Kbytes (Mono)

Receive Buffer

4 Kbytes

User Define Buffer

12 Kbytes

Interface

Standard: USB 2.0 FS

Optional: ① USB 2.0 FS + Serial

② USB 2.0 FS + Parallel

③ USB 2.0 FS + Ethernet

④ USB 2.0 FS + Dual Serial
(KOR Only)

Environment Characteristics

Temperature

Operating: 0 to 40°C (32 to 104°F)

Storage: -20 to 60°C (-4 to 140°F)

Humidity

Operating: 10 to 80% RH

Storage: 10 to 90% RH

Software

Emulation

BXL/POS™

Driver/Utility

Windows® Driver, OPOS/JPOS Driver,

Linux®/macOS® CUPS Driver,

Virtual COM USB/Ethernet Driver

Utility Program, Network Auto Installer

Developer Tools

Android™/iOS®/Windows SDK, Linux SDK,

Xamarin SDK, Web Print SDK

(Android/iOS/Windows/macOS)

Cordova Plugin, MAUI SDK, Flutter™ Plugin,

React Native SDK,

B-gate SDK_Cloud Server Print,

B-gate SDK_Web App Print

Design & Print

mPrint App (Android/iOS),

Cloud Server Print, Web App Print

MDM(Optional)

BIXOLON Profile Manager - XPM™,

XCM™ (Windows/Android)

Fonts/Graphics/Symbologies

Character Size

Font A: 12 x 24, Font B: 9 x 17,

Font C: 9 x 24, KOR, CHN, JPN: 24 x 24

Characters per Line

Font A: 48,

Font B, C: 64, KOR, CHN, JPN: 24

Character Sets

Alphanumeric: 95

Extended Graphics: 128 x 35 page

International: 32

Barcode Symbologies

1D: Coda Bar, Code 39, Code 93,

Code 128, EAN-8, EAN-13, ITF,

UPC-A, UPC-E

2D: Data Matrix, GS1-128,

GS1 DataBar Stacked/

Omnidirectional/Truncated/

Limited/Expanded, PDF417, QR code

Accessories/Supplies

Included in the Box

Paper, AC/DC Adapter, Cable Cover,

Power Cord, USB A-B Cable 1.8 m

Options & Accessories

Built-in AC/DC Adapter, Vertical Stand,

Wall Mount, Splash Proof Cover,

External Buzzer, B-Melodist,

Serial Cable (9-9/25-9 pin),

Parallel Cable, 2-inch Partition (58 mm)